PRE-INSPECTION FIRE CHECKLIST

Fire inspectors look at many items in your place of business. So that you may have a better idea and understanding of what to keep an eye on in regard to maintenance, we have provided the following checklist:

A. EXITS	
Door/aisle is not obstructed Illuminated exit signs maintained in working order.	
Proper lock/hardware on exit door Means of egress shall be kept clear.	
(No flush bolts, hasps, etc.) Emergency lights maintained and in working order.	
Exit doors open easily Doors with panic hardware shall have no other locking	devices.
There is a sign over the main entrance, "This door Maximum occupancy signage shall be posted in a consp	oicuous
to remain unlocked during business hours," if the location near the main entrance for assembly occupanci	es.
door has a double-keyed deadbolt.	
B. EXTINGUISHERS/FIRE PROTECTION EQUIPMENT	
Minimum 2A10BC extinguisher(s) installed Hood extinguishing system maintained, and six month	
Extinguisher has been serviced within the past service and cleaning documented.	
year and a new service tag is attached Class K extinguisher installed within 30' of hood and defined the control of the	•
Extinguisher is securely mounted or in an Fire alarm system in proper working order – system test	ed
approved cabinet. annually and records kept.	
Fire extinguisher not obstructed 18" clearance between storage and sprinkler head.	
Fire extinguisher top does not exceed 5' from Sprinkler system shall be maintained and tested annuall	y.
floor as mounted Private hydrants (painted red) maintained – flushed year	:ly
Standpipe shall be tested every 5 years. and flows taken every three years.	
C. ELECTRICAL	
No extension cords in use in place of permanent Electrical panel is not overloaded/obstructed.	
wiring. No multi-plug adapters in use, other than approved	
There are no spliced or frayed cords/wires. power strips.	
Spacer(s) in electrical panel gap(s) provided Circuit breakers are labeled.	
No broken or faulty switch/outlets Electrical cords do not extend through walls, ceilings ar	ıd

	No exposed wire in conduit. No missing/broken electrical cover plate(s).		floors or under doors or floor coverings. 30" clearance maintained in front of electrical panels.	
D. <u>Al</u>	PPLIANCES/MECHANICAL DEVICES No propane used/stored in building.		All appliances are properly connected and vented.	
E. STORAGE/COMBUSTIBLE MATERIAL/HOUSEKEEPING				
	Flammable liquid properly stored.		No accumulation of combustible materials.	
	Oil rags in con-combustible container with lid.		Compressed gas cylinders secured.	
	"No Smoking" signs installed as required.		Area around building free of combustible material	
	No combustible material stored near ignition		(weeds, trash, boxes, etc.).	
	source.		No storage shall be kept in exit stairways.	
	Maintain clear and visible access to and around		Fire and smoke walls shall be maintained and have	
	fire department connection.		no opening other than those allowed by code.	
F. MISCELLANEOUS				
	Fire lanes shall be approved by the fire department.		Rapid key entry box maintained by property owner.	
	(Mark Sweany, 913/438-4888, ext.238)		Charcoal grills, propane grills and/or other open-flame	
	Address numbers shall be posted in contrasting		cooking devices shall not be located on combustible	
	colors on front and rear doors for commercial		balconies or within 10' of combustible construction.	
	businesses and shall be 8" on the front door, 4" on		EXCEPTIONS : 1) One and two family dwellings, and	
	back doors. All other structures shall be 4" except		2) Where balconies/decks are protected by an automatic	
	home daycares, which shall be 6".		sprinkler system.	

NOTE: This list is a general guideline only for common violations that can be readily determined by the occupant.